



Product Name: External One Port GNSS Antenna

Part Number: EG-6AB-DS-A01

Features:

- Support GPS L1 / GLONASS L1/ BeiDou L1/ GPS L2 Bands
- Excellent Out of Band Rejection, Up to 70dB
- 40 dB Active Peak Gain
- Customizable Cables and Connectors
- RoHS & REACH Compliant

Applications:

- Automotive Navigation
- For all GNSS applications with networking such as sensor, sonar multi-function gauge, etc.

External One Port GNSS Antenna

MODEL: EG-6AB-DS-A01

Rev.A

I. Specifications:


Items	Specifications			
Passive Antenna Performance				
Application Bands	GPS L2	BeiDou L1	GPS L1	GLONASS L1
Frequencies (MHz)	1227	1561	1575.42	1602
Efficiency (%)	6.78	54.58	43.95	29.04
Average Gain (dBi)	-11.69	-2.63	-3.57	-5.37
Peak Gain (dBi)	-11.69	3.24	2.48	0.69
Axial Ratio	1.29	2.24	2.16	2.38
V.S.W.R	< 2			
Return loss (dB)	< -10			
Test Condition	Free Space			
Impedance (Ω)	50			
Polarization	R.H.C.P. (Right-Handed Circular Polarization)			
Active Antenna Performance				
Application Bands	GPS L2	BeiDou L1	GPS L1	GLONASS L1
Frequencies (MHz)	1227 \pm 5	1561 \pm 5	1575.42 \pm 1.023	1602 \pm 5
Gain (dB)	40 Typ.			
Noise Figure (dB)	1.5 Typ.			
Operation Voltage (V)	3.3 ~ 5.0			
Current Consumption (mA)	20 \pm 3			
Output Impedance (Ω)	50			

© Unictron Technologies Corp.
All specifications subject to change without notice.


Out of Band Rejection				
Application Bands	GPS L2		BeiDou L1 GPS L1 GLONASS L1	
Frequencies (MHz)	600 ~ 1100	1330 ~ 1520	1330 ~ 1520	1650 ~ 3000
Out of Band Rejection (dB)	58	60	60	70
ESD Protection	+/- 8 KV (direct discharge) +/- 15KV (air discharge)			
Mechanical				
Dimension (mm)	φ 80.0(D) x 90.0(L) x 25.4(H)			
Waterproof	IP67			
Cable / Length	H-100 / 3 meters			
Connector	SMA (Male)			
Environmental Conditions				
Operation Temperature (°C)	-40 ~ +85			
Storage Temperature (°C)	-40 ~ +85			
Relative Humidity	95% non-condensing			

II. Passive Electrical Properties:


S11 (dB)




Efficiency (%)



Average Gain (dBi)





Peak Gain (dBi)




III. Active Electrical Properties:

Noise Figure & Gain (dB)




Out of Band Rejection (dB)



© Unictron Technologies Corp.
All specifications subject to change without notice.

IV. Antenna Radiation Pattern Measurement:


The antenna radiation patterns are measured in 3D Anechoic Chamber. The measurement setup is as show below,





© Unictron Technologies Corp. All specifications subject to change without notice.

A) 2D Radiation Pattern:



X-Y Plane



X-Z Plane




Y-Z Plane





B) 3D Radiation Pattern:

1227MHz




1561MHz





V. Mechanical Drawing (Unit:mm):



10	Rubber stopper	EPDM	Black	2
9	Slip Rubber	Silicone	Black	4
8	Screw	Stainless Steel	Cr	4
7	Label	PET	Silver	1
6	Cable Rubber	EPDM	Black	1
5	Heat Shrink Tube	EVA	Black	2
4	SMA(M) Connector	Brass	Au Plated	3
3	Cable H-100	PVC	Black	3
2	Bottom Base	Zinc Alloy	Ni Plated	1
1	Top Housing	PC+ABS	Black	1
No	NAME	MATERIAL	FINISH	Q'TY