

11

5. Layout Guide & Electrical Specifications

5-1. Layout Guide (unit : mm)

Solder Land Pattern:

The solder land pattern (gold marking areas) is shown below. Recommendation on matching circuit will be provided according to customer's installation conditions.



11

5-2. Electrical Specifications (Evaluation Board Dimensions: 80 x 40 mm²) 5-2-1. Electrical Table

Characte	ristics	Specifications	Unit		
Outline Dimensions		3.2 x 1.6 x 0.5	mm		
Ground Plane Dime	nsions	80 x 40	mm		
Working Frequency		2400~2500	MHz		
VSWR (@ center fre	equency)*	2 Max.			
Characteristic Imped	dance	50	Ω		
Polarization		Linear Polarization			
Peak Gain	(@2442 MH-)	2.5 (typical)	dBi		
Efficiency	(≝∠442 №ΠΖ)	84 (typical)	%		

*Center frequency means the frequency with the lowest value in return loss of the chip antenna on the evaluation board.









- 11

7. Radiation Pattern (with 80 x 40 mm² Evaluation Board)

7-1. 3D Gain Pattern @ 2442 MHz (unit: dBi)









Document Control Cente



詠業科技股份有限公司 Unictron Technologies Corporation

Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Xenia	Designed by : Phillip	Checked	by : Mike	Approved by : Herbe				
TITLE:WiFi/Bluetooth C	Ceramic Chip Antenna (AA055A)	DOCUMENT	H2B1BG2A	A1B010			REV.	
with Evaluation	Board Engineering Specification	NO.					Α	
			PAGE	. 7		OF	11	

7-2. 3D Efficiency Table																
Frequency(MHz)	2400	2412	2417	2422	2427	2432	2437	2442	2447	2452	2457	2462	2467	2472	2484	2500
Efficiency(dB)	-1.4	-1.0	-0.9	-0.8	-0.8	-0.8	-0.7	-0.7	-0.8	-0.8	-0.8	-0.9	-0.9	-1.0	-1.2	-1.4
Efficiency(%)	72.8	78.7	80.4	82.3	83.0	83.9	84.4	84.5	84.1	84.0	83.2	82.0	80.5	78.6	75.4	72.5
Peak Gain(dBi)	1.5	1.8	1.9	2.1	2.3	2.3	2.4	2.5	2.5	2.5	2.4	2.4	2.2	2.1	1.9	1.8





Frequency tuning and Matching circuit 8. 8-1. Chip antenna tuning scenario : 4. Fine tuning element Signal Input Matching circuit 8-2. Matching circuit : With the following recommended values of matching and tuning components, the center frequencies will be about 2442 MHz at our standard 80x40 mm² evaluation board. However, these are typical reference values which may need to be changed when circuit boards or part vendors are different. System Matching Circuit Component Location Description Vendor Tolerance IN 1 1.2pF, (0402) DARFON ±0.1 pF GND DC Block -----IN 2 2 3.3nH, (0402) DARFON ±0.1 nH 4 3 Jnictron_ 3 N/A 4 Fine tuning 1.2pF, (0402) DARFO2016-1-0-18F element THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES 詠業科技股份有限公司 CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR Unictron Technologies Corporation SALE OF APPARATUS OR DEVICES WITHOUT Technologies Corp. Website:www.unictron.com PERMISSION Prepared by : Xenia **Designed by : Phillip** Checked by : Mike Approved by : Herbert DOCUMENT TITLE: WiFi/Bluetooth Ceramic Chip Antenna (AA055A) REV. H2B1BG2A1B0100 with Evaluation Board Engineering Specification NO. Α PAGE 9 OF 11



9. Reminders for users of Unictron's AA055A ceramic chip antennas

- 9-1. This chip antenna is made of ceramic materials which are relatively more rigid and brittle compared to printed circuit board materials. Bending of circuit board at the locations where chip antenna is mounted may cause the cracking of solder joints or antenna itself.
- 9-2. Punching/cutting of the break-off tab of PCB panel may cause severe bending of the circuit board which may result in cracking of solder joints or chip antenna itself. Therefore break-off tab shall be located away from the installation site of chip antenna.
- 9-3. Be cautious when ultrasonic welding process needs to be used near the locations where chip antennas are installed. Strong ultrasonic vibration may cause the cracking of chip antenna solder joints.

10. Operating & Storage Conditions

- 10-1. Operating
 - (1) Maximum Input Power: 2 W
 - (2) Operating Temperature: -40 $^\circ\!\mathrm{C}$ to 85 $^\circ\!\mathrm{C}$
- 10-2. Storage
 - (1) Storage Temperature: $-5^{\circ}C$ to $40^{\circ}C$
 - (2) Relative Humidity: 20% to 70%
 - (3) Shelf Life: 1 year

11. Notice

All specifications are subject to change without notice.

